

Ramset LADD Pin and Clip

Pre-tied Wire Assemblies


- Ramset LADD Pin and Clip
- Assembly Part # RAM-L652
- Pre-tied Part # PT_ _ L652

**Many other manufactured and custom assemblies are available.
Contact CEAS for more ordering options!**

**Actual pre-tied wire lengths are roughly 6" shorter than the length specified due to the wrap*



ATTACHMENTS



Note: If ordering single wire tie, you do not need to fill in column C

C = Add "D" for Double Tie or "T" for Triple Tie

| | | | |
|--|--|---------------------------|--|
| Contractor: | | Project Name and Address: | |
| | | | |
| | | | |
| PO# | | Order Date: | |
| **All Orders are Custom and Therefore Non-cancellable and Non-returnable | | | |

| | A | B | | C | Qty |
|----|----------------|------------|--------|-----------|-----|
| | Length in Feet | Wire Gauge | Part # | Wire Ties | |
| PT | | | L652 | | |
| PT | | | L652 | | |
| PT | | | L652 | | |



How To Order

Step A - Determine the Wire Length

**Actual pre-tied wire lengths are roughly 6" shorter than the length specified due to the wrap*

Step B - Determine the Wire Gauge (12g typ)

8 Gauge (.162)
9 Gauge (.147)
10 Gauge (.135)
12 Gauge (.105)



8, 9, 10 and 12 gauge wire
typical tensile strength
= 70ksi (Meets ASTM A 641 Specs)

PT _ _ L652 _ _
Step A Wire Length Step B Wire Gauge Step C Wire Tie(s)

Step C - Choose Single. Double or Triple Tie

Add "D" for Double Tie or "T" for Triple Tie to the end of the part number when ordering



Part Number Example #1: **PT612L652** = Pre-Tied, 6' Long, 12g Wire, Ramset LADD Pin and Clip

Part Number Example #2: **PT612L652D** = Pre-Tied, 6' Long, 12g Wire, Ramset LADD Pin and Clip, Double Tie



CONSTRUCTION ENGINEERED ATTACHMENT SOLUTIONS - It's What We Do!

© 2018 CEAS, All Rights Reserved • 14848 Northam St., La Mirada, CA 90638 • Tel: 877-GOO-CEAS • Fax: 714-522-3648